

99005,99006

INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions as you may need them a later date.

CAUTION

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor.

Turn off the main power at the circuit breaker before installing the fixture in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code(N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are

ASSEMBLY AND INSTALLATION

1. Adjust the position of each lamp arm as left image of drawing.
2. Determine the desired hanging height and connect stems(13, 14 and 15). Connect stem(15) to stem(16) on the top of the fixture body, and then connect stem(13) to swivel(12). Pass the wires carefully through each stem when you assemble.
3. Secure the mounting plate(7) to the outlet box(1) with the outlet box screws(9).
4. Pull out the source wires from the outlet box(1). Make wire connections using wire caps(6) as follow:
 - Connect the smooth-coated wire(marked) from the fixture to the black wire from the power source.
 - Connect the ribbed-coated wire(unmarked) from the fixture to the white wire from the power source .
 - Attach the fixture ground wire to mounting plate(7) with the ground screw(5). Connect it to the house ground wire with the wire cap(6).Carefully tuck the connected wires back into the outlet box(1).
5. Align the canopy(10) to the outlet box(1), then secure it to the mounting plate(7) with the finials(11).
6. Install bulbs: (bulbs not included)
(Don't exceed the maximum capacity recommended on the Sockets).

INSTALLATION IS NOW COMPLETED

